


CM20DT

6.5" two-way, thin edge ceiling
loudspeaker, white



The CM20DT 6.5" two-way built-in loudspeaker can be used in 16 ohms or 70/100 volt modes. The high-quality 70/100 volt transformer is equipped with an easy tapping sticker with clear colour indication. The transformer colours are aligned with the cables connecting the Apart Quick Fit connector, a handy installer connector via push terminal.

In 16 ohms use, you can connect up to 4 loudspeakers in parallel on each channel of a standard 4 ohms amplifier. The paintable thin edge grille makes CM20DT the ultimate loudspeaker for design interior integration.

TECHNICAL SPECIFICATIONS

outside diameter in mm	210	depth in mm	80
cutout in mm	186	loudspeaker system	2-way
woofer size in inch	6.5	woofer cone material	polypropylene
tweeter size in inch	1	mounting system	3 screws
colour	white	100V transformer power taps in watts	20 - 10 - 5
70V transformer power taps in watts	20 - 10 - 5 - 2.5	impedance in ohms	16
low impedance dynamic power in watts	60	SPL 1W/1m in dB	86
max SPL 1m in dB	104	frequency response in Hz	60 - 20K
main construction material	ABS plastic	grille main material	steel
IP rating	50	applicable low impedance	yes
applicable in 100V	yes	Vertical dispersion angle 1000 Hz	180°
Net weight product in kg	1.24		

MORE PICTURES

