

DriveRack™ 260

Complete Equalization & Loudspeaker Control System

dbx®
PROFESSIONAL PRODUCTS

VISIONARY DESIGN

The DriveRack™ 260 was designed to provide state-of-the-art signal processing, while maintaining a simple and intuitive control interface. This goal has been realized. From the powerful DSP modules to the multiple control surfaces, the 260 provides all the processing and control necessary for both installation and live use. Additionally, the Wizard function enables any user to quickly set up and use the 260 to its full potential by streamlining the setup process and providing a menu based setup procedure that includes system setup and configuration, Auto-EQ, and Advanced Feedback Suppression™ (AFS™) setup.

REVOLUTIONARY ENGINEERING

The DriveRack™ 260 is based on the same unparalleled design philosophy as the other products in the DriveRack™ family, namely, to provide "Everything you need between the mixer and the power amps". In keeping with that philosophy, the 260 offers two inputs and six outputs on XLR connectors. Each input channel provides a choice of EQ, either a 9-band Parametric or a 28-band Graphic EQ. Each input channel also boasts two selectable insert processors with a selection of Notch Filtering, classic dbx® Compression, Auto Gain Control, Sub-Harmonic Synthesis, or our own patent-pending Advanced Feedback Suppression™ (AFS™). **The DriveRack™ 260 also offers a configurable Delay with 2.7 seconds of total delay time.** The 260 provides full Bandpass and Crossover filtering and routing including Bessel, Butterworth and Linkwitz-Riley topologies. There is Parametric EQ available on each output as well as dbx® PeakStopPlus™ Limiting. The 260 provides a full-time RTA for live sound applications, while contractors will appreciate its control inputs for wall-panel logic and volume control. For more information please visit www.driverack.com or www.dbxpro.com.

FEATURES

- **Feedback Elimination**
- **2.7 Seconds of Delay**
- **RS-232 PC GUI control**
- **Classic dbx® Compression and Limiting**
- **Graphic and Parametric EQ**
- **Auto-EQ Function**
- **Full Bandpass, Crossover, and Routing Configurations**
- **Auto Gain Control**
- **Pink Noise Generator and RTA**
- **Setup Wizard with JBL® Speaker and Crown® Power Amplifier Tunings**
- **Security Lockout**
- **Wall Panel Control Inputs**
- **IEC, UL and CSA Approvals**

8760 S. Sandy Pkwy.
Sandy, Utah 84070
Phone (801) 568-7660
Fax (801) 568-7662
Int'l Fax (801) 568-7583
customer@dbxpro.com
<http://www.dbxpro.com>

H A Harman International Company



DriveRack™ 260

Complete Equalization & Loudspeaker Control System



SPECIFICATIONS

Analog Inputs:

Number of Inputs: (2) Line inputs, (1) RTA Mic input
Connectors: (2) Female XLR line inputs, XLR RTA Mic input
Type: Electronically balanced/RF filtered
Impedance: > 40k Ω
Max input line level: +34dBu with input jumpers in +30 position
CMRR: > 45dB
RTA Mic Phantom Voltage: +15VDC
RTA Mic EIN: < -110dBu, 22Hz-22kHz, 150 Ω

Analog Outputs:

Number of Outputs: 6
Connectors: Male XLR
Type: Electronically balanced, RF filtered
Impedance: 120 ohms
Max Output Level: +22dBu

A/D Performance:

Type: dbx Type IV conversion system
Dynamic Range line: >114 dB A-weighted, >112 dB unweighted
Type IV dynamic range: >119 dB, A-weighted, 22kHz BW
Sample Rate: >117 dB, A-weighted, 22kHz BW
48kHz

D/A Performance:

Dynamic Range: 112 dB A-weighted, 110dB unweighted

System Performance:

Dynamic Range: >110 dB unweighted, >107dB weighted,
THD+N: 0.002% typical at +4dBu, 1kHz, 0dB input gain
Frequency Response: 20Hz – 20kHz, +/- 0.5dB
Interchannel Crosstalk: >110dB, 120dB typical
Crosstalk input to output: >100dB

Safety Agency Approvals:

UL 6500, IEC 60065, EN 55013, E 60065

dbx engineers are constantly working to improve the quality of our products. Specifications are, therefore subject to change without notice.

FOR MORE INFORMATION CONTACT:

dbx Professional Products
8760 S. Sandy Pkwy.
Sandy, Utah 84070
Phone (801) 568-7660
Fax (801) 568-7662
customer@dbxpro.com
<http://www.dbxpro.com>

dbx PROFESSIONAL PRODUCTS

The Professional's Choice In Signal Processing™

■ A Harman International Company