



AC895

2-Way Full-Range Loudspeaker
with 1 x 8" LF

Key Features:

- Compact enclosure
- 209 mm (8 in) LF transducer
- 90° x 50° Progressive Transition™ Field Rotatable Waveguide with a 25 mm (1 in) exit 25mm (1") voice-coil compression driver
- Dual Neutrik NL4 connectors plus screw terminals
- Multiple Attachment Points for Ultimate Flexibility

Applications:

- Performing Spaces
- Clubs & Bars
- Houses of Worship
- Multi Media Spaces
- Retail & Hospitality Spaces
- Presentation Suites
- Educational Facilities

AC895 is a compact 2-way full-range loudspeaker system comprised of one 209 mm (8 in) low frequency driver and one 25 mm (1 in) exit/25 mm (1 in) voice-coil compression driver. The rotatable PT™ Progressive Transition waveguide provides 90° by 50° coverage in vertical cabinet orientation. High-slope passive crossovers minimize band overlap and well-controlled offaxis response.

The cabinet is fitted with M10 threaded suspension points. Four threaded inserts located on back of the enclosure allow attachment of a MultiMount® or similar type mounting.

AC895 is part of JBL's AE Application Engineered Series, a versatile family of loudspeakers for a wide variety of fixed installation applications.



Specifications:

System:

Frequency Range (-10 dB) ¹ :	70 Hz - 20 kHz
Frequency Response (± 3 dB) ² :	90 Hz - 18kHz
System Sensitivity (1w @ 1m) ³ :	94 dB
Nominal Impedance:	8 ohms
Maximum SPL(1m) ² :	116 dB (122 dB peak)
Power Rating ³ :	150 W/300 W/600 W
Coverage Pattern:	90° x 50° (H x V)
Crossover:	2 kHz

Transducers:

Low frequency driver:	1 x 8" woofer (P/N: 5055470), 209 mm (8 in) driver with 50 mm (2 in) voice-coil
High frequency driver:	1 x 2414H-C driver with 25 mm (1 in) exit/25 mm (1 in) voice-coil

Physical:

Input Connector:	Dual Neutrik NL4MP connectors plus covered barrier trip terminals
Enclosure:	15 mm multi-ply hardwood plywood
Grille:	Powder coated, 1.5mm perforated steel, with acoustically transparent black foam backing
Finish:	Textured black paint finish. White (-WH) available upon request. Not available with WRC & WRX finish.
Suspension / Mounting:	14 x M10 and 4 x M10 for Wall Mount Bracket. Optional U-bracket, L-bracket and wall-mount bracket
Dimensions (H x W x D):	470 mm x 265 mm x 254 mm 18.5 in x 10.4 in x 10.0 in
Net Weight:	10.2 kg (22.4 lbs)



¹ Full space (4π) conditions

² Calculated maximum SPL based on rated power handling

³ IEC shaped pink noise with 6dB CF for 100hrs






JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

► AC895 2-Way Loudspeaker with 1 x 8" LF



Dimensions:

Dimensions in mm (inch)



PROFESSIONAL
by HARMAN

JBL Professional
8500 Balboa Boulevard, P.O. Box 2200
Northridge, California 91329 U.S.A.

© Copyright 2015 JBL Professional
www.jblpro.com

AC895
SZ
04/15